

GENMANN

GENERATORS



Planta Eléctrica Diesel 20KW Trifásico
Diesel Generator Set 20KW three phase

Modelo Model	GMD20-4TNV88-3
Kw Emergencia Stand by Kw.	20
Kw Continuo Prime Kw.	19
Voltaje Voltage	220 / 440
Max. Amp.	65 / 32
Hz.	60
Motor	Yanmar 4TNV88-GGE
HP / R.P.M.	29 / 1800
Cilindros Cylinders	4 en linea 4 Inline
Desplazamiento Displacement	2.18 Lts.
Sistema de Combustion Combustion System	Inyeccion Indirecta. Indirect injection.
Aspiracion Aspiration	Natural
Sistema de Enfriamiento Cooling System	Agua Water

Generador Generator	Stamford BCI184E
Regulador de Voltaje AVR.	SX460
Num. Puntas Leads	12
Aislamiento Insulation	Clase H Class H
Fases Phase	3
Factor de Potencia Power Factor	0.8
Cosumo de Combustible a plena carga Fuel consumption at full load	5.8 Lt./Hr.
Capacidad del tanque de diesel Diesel tank capacity	80 Lt.
Largo Length	1500 mm
Ancho Wide	676 mm
Alto Height	1150 mm
Peso Weight	376 kg.